



SEMPERIT 

SAE 100 R 16-S



Компактный Гидравлический Рукав конструкция соответствует SAE 100 R16-S



РВД:	
Внутренний слой	Синтетический каучук, стойкий к гидравлическим жидкостям (HL, HLP, HLPD, HVLP, HFA, HFAS, HFB, HFC)
Усиление	Две оплетки из высокопрочной стальной проволоки
Оболочка	Стойкий к воздействию абразивов и озона синтетический каучук. Примечание: в наличие имеются различные оболочки
Диапазон температур	-40°C to 100°C (Кратковременно макс 120°C)
Стандартная маркировка	тиснение

SEMPERIT® SAE100 R16 S -06 3/8" WP 330 BAR 4780 PSI . Q . . W . . z

Номинальный Ø		Внутрен Ø	Оплетка Ø	Внешний Ø	Рабочее давление		Давление испытания	Давление разрыва	Радиус Изгиба	Вес
mm	inch	mm	mm	mm	bar	psi	bar	bar	mm	kg/m
6	1/4	6,6	11,7	13,7	400	5800	800	1600	50	0,25
8	5/16	8,3	13,0	15,0	350	5075	700	1400	55	0,27
10	3/8	9,9	15,1	17,0	330	4780	660	1320	65	0,36
12	1/2	13,0	18,3	20,5	275	3980	550	1100	90	0,46
16	5/8	16,4	21,9	23,9	250	3620	500	1000	100	0,63
19	3/4	19,5	25,5	27,7	215	3110	430	860	120	0,78
25	1	26,0	32,7	35,3	165	2390	330	660	150	1,16

Дата публикации: Апрель 2013 - Возможны изменения характеристик без предупреждения

Important Notice:

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The choice of the correct type of hose is very important for the proper and safe use in service. Check your or your customer's specific application accordingly and instruct on limits and dangers of product use accurately. Application, use and processing of our products or your products manufactured on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Check for operating safety regularly. In the event of damage, in particular to the hose cover, hoses must be replaced for safety reasons. **Caution/Danger:**

Wrong product selection, installation or improper treatment (such as crushing, tearing, stretching, loading with impermissible media and bending radius lower than specified) of the hoses can result in damage or failure of the hose, (often also serious) material damage and personal injury.

semperflex® 
HYDRAULICS

A MEMBER OF THE SEMPERIT-GROUP